PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT

		INDER THE PATENT COUPERATION TREATY (PCI)
(51) International Patent Classification 6:		(11) International Publication Number: WO 97/3356
A01K 9/20	AZ	(43) International Publication Date: 18 September 1997 (18.09.9)
(21) International Application Number: PCT/US (22) International Filing Date: 28 February 1997 ((30) Priority Data: 60/013,290 12 March 1996 (12.03.96) (71) Applicant: ALZA CORPORATION [US/US]; 950 F Road, P.O. Box 10950, Palo Alto, CA 94303-0802 (72) Inventors: KUCZYNSKI, Anthony, L.; 777 West Mi Road #157, Mountain View, CA 94043 (US). CH Jerry, D.; 1313 Socorro Avenue, Sunnyvale, C. (US). BARCLAY, Glen, E.; Unit C, 441 Mariposa Mountain View, CA 94041 (US). ROGRIGUEZ 816 Lathrop Drive, Stanford, CA 94305 (US). Mi Sonya; 5002 Paseo Olivos, San Jose, CA 95130 (UC) (74) Agents: SABATINE, Paul, L. et al.; Alza Corporat Page Mill Road, P.O. Box 10950, Palo Alto, CA 0802 (US). (54) Title: COMPOSITION AND DOSAGE FORM COM (57) Abstract A composition of matter is disclosed and claimed coa poly(carboxymethylcellulose). A dosage form is disclose	Page M. 2 (US). iddlefie: ILDER: A 9408 Avenu. Z. Susai ERRILI JS). ion, 95 A 94303	(43) International Publication Date: 18 September 1997 (18.09.97) (81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BF, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GF, HU, IL, IS, IP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, UZ, VN, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG) Published Without international search report and to be republished upon receipt of that report.
analgesic from the dosage form.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
ΑŬ	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgystan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic	SD	Sudan
CF	Central African Republic		of Korea	SE	Sweden
CG	Congo	KR	Republic of Korea	SG	Singapore
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LR	Liberia	SZ	Swaziland
CS	Czechoslovakia	LT	Lithuania	TD	Chad
cz	Czech Republic	LU	Luxembourg	TG	Togo
DE	Germany	LV	Latvia	TJ	Tajikistan
DK	Denmark	MC	Monaco	TT	Trinidad and Tobago
EE	Estonia	MD	Republic of Moldova	ŲA	Ukraine
ES	Spain	MG	Madagascar	UG	Uganda
FI	Finland	ML	Mali	US	United States of America
FR	France	MN	Mongolia	UZ	Uzbekistan
GA	Gabon	MR	Mauritania	VN	Viet Nam

WO 97/33566 PCT/US97/03110

COMPOSITION AND DOSAGE FORM COMPRISING

OPIOID ANTAGONIST

FIELD OF THE INVENTION

This invention pertains to a novel composition comprising an opioid antagonist. This invention also concerns a novel dosage form comprising an opioid antagonist. The invention further concerns a method of administering a dosage form comprising an opioid antagonist for lessening the incidence of drug abuse.

BACKGROUND OF THE INVENTION

24 .

Analgesics are drugs which relieve pain and they act to relieve pain by elevating the pain threshold of a patient in need of pain relief. One group of analgesic drugs are the opiates. The opiate group of analgesics are among the most powerfully acting and clinically useful drugs for the relief of pain. The term opiate was once used to designate analgesic drugs derived from opium including morphine, codeine and synthetic congeners of morphine. With the development of totally synthetic drugs with morphine-like actions, the word opioid is used to refer to all drugs, both natural and synthetic, with morphine-like actions. The term narcotic as associated with the opioids, refers to the physical dependence accompanying the use of these drugs and with their increasing use it refers to opioid substances that cause dependence.

In addition to their many important medical uses, the opioid drugs are employed commonly for illicit purposes, including emotional, psychological, euphoric, hallucinogenic, depressive, and psychedelic experiences. These purposes and the physical dependence accompanying the administration of these drugs has led to drug abuse. Drug abuse has become for many

- habituates a way of life. To a rapidly growing segment of the world
- population, use of these drugs is a vogue often seen as fashionable.
- While these drugs are a necessary part of modern medicine, it would be
- highly desirable to provide a novel drug delivery system and a novel
- 5 composition of matter that do not possess drug abuse potential, and thereby
- seek to lessen the incidence of their abuse and their illicit use.

SUMMARY OF THE INVENTION

In view of the foregoing, it is apparent that a pressing need exists for an improved delivery of opioids for their therapeutic effects, while concomitantly substantially lessening or substantially preventing opioid abuse. Thus, it is an object of this invention to provide a composition of matter indicated for use in a dosage form comprising an abusable opioid, which composition imparts a low potential for abuse of both the composition and the dosage form comprising same. Another object of the invention is to provide a dosage form comprising a first composition containing an opioid and a second composition separate and distinct from the first composition containing an antagonist for lessening opioid abuse.

DETAILED DESCRIPTION OF THE INVENTION

The term opioid as used for the purpose of this invention represents an opioid member selected from the group consisting of alfentanil, allylprodine, alphaprodine, apomorphine, anileridine, apocodeine, benzylmorphine, bezitramide, buprenorphine, butophanol, clonitazene, codeine, cyclorphan, cyprenorphine, desomorphine, dextromoramide, dezocine, diampromide, dihydrocodeine, dehydromorphine, diminoxadol, eptazocine, ethylmorphine, fentanyl, hydrocodone, hydroxymethylmorphian, hydromorphone, hydroxypethidine, levophenacylmorphan, levorphanol, lofentanil,

- methylmorphine, morphine, necomorphine, normethadone, normorphine,
- opium, oxycodone, oxymorphone, pholcodine, profadol, and sufentanil.
- 3 The opioid can be present as a member selected from the opioid base and
- 4 the opioid pharmaceutically acceptable salt. The pharmaceutically
- acceptable salt embraces the inorganic and the organic salt. Representative
- salts include a member selected from the group consisting of hydrobromide,
- 7 hydrochloride, mucate, succinate, n-oxide, sulfate, malonate, acetate,
- 8 phosphate dibasic, phosphate monobasic, acetate trihydrate,
- 9 bi(heplafluorobutyrate), maleate, bi(methylcarbamate),
- bi(pentafluoropropionate), mesylate, bi(pyridine-3-carboxylate),
- bi(trifluoroacetate), bitartrate, chlorhydrate, fumarate, and sulfate
- pentahydrate. The dose of opioid, in the first or opioid composition,
- is 75 ng to 750 mg.
- The antagonist present in the second, or antagonist composition, is an
- effective amount to attenuate, that is to lessen and/or reduce the effect of the
- opioid present in the first composition. The antagonist is present in 10 ng to
- 17 275 mg, or 0.75 to 10 wt%, in the second or antagonist composition that is
- separate and distinct from the first or opioid composition. The antagonist is
- an opioid antagonist selected from the group consisting of naltrexone,
- naloxone, nalmefene, nalide, nalmexone, nalorphine, nalpuphine, nalorphine
- dinicotinate, and the pharmaceutically acceptable base, the pharmaceutically
- 22 acceptable salt thereof. The pharmaceutically acceptable addition salt
- embraces those presented earlier in the specification.

MODES OF PERFORMING THE INVENTION

EXAMPLE 1

A novel dosage form for delivering hydrocodone to a patient in need of pain relief is prepared as follows: first, 24.8g of hydrocodone bitratrate hemipentahydrate, 70.3g of poly(ethylene oxide) of 200,000 average number molecular weight, available from Union Carbide Institute, West Virginia, and 5.0 mg of hydroxypropylmethylcellulose possessing a 11,200 average number molecular weight available from Dow Chemical Co., Midland, Michigan, are dry blended for 5 minutes using a roll mill. Then, 50 ml of denatured ethyl alcohol are added to the dry blend, and slowly mixed together for 5 minutes. After drying at room temperature, the mass is pressed through a 0.0331 inch (0.85 mm) screen, and then dried further at room temperature overnight. Next, 0.5 mg of magnesium stearate is blended with the granulation for 2 minutes to produce a homogenous blend.

Next, a second or antagonist composition is prepared as follows: first, 30.8g of poly(ethylene oxide) of 7,000,000 number average molecular weight, 15.0g of sodium chloride, and 3.0g of hydroxypropylmethylcellulose of 11,200 number average molecular weight, and 0.4g of naloxone, and 1.0g of ferric oxide are blended homogeneously in the presence of denatured alcohol. The homogenous mass is pressed through a 0.0469 inch (1.19 mm) screen and dried overnight at room temperature, and then pressed through a 0.0331 inch (0.85 mm) screen. Then, 1.0 mg of lubricant is added to the gran; lation. Then, 450 mg of the first composition and 250 mg of the second composition are pressed in a standard tablet press into a bilayer core with the first composition and the second composition in bilayered arrangement. The bilayered core comprises an oval shape 0.700 inches (1.78 cm) by 0.375 inches (0.95 cm).

The bilayered core is coated with a semipermeable membrane consisting of 40 mg of cellulose acetate of 39.8% acetyl and 2 mg of polyethylene glycol 3350. The membrane-forming composition is dissolved in acetone:water (95:5 wt:wt), and the wall-forming composition is sprayed around the bilayered core in a coater. Next, two 30 mil (0.762 mm) exit passageways are drilled through the semipermeable membrane to connect the opioid drug layer with the exterior of the dosage form. Finally, the dosage form is dried for 48 hours at 50° to remove excess moisture.

9°

EXAMPLE 2

A dosage form is provided by the invention by first preparing a morphine composition wherein 17.28g of morphine sulfate pentahydrate, 38.52g of poly(ethylene oxide) possessing a 200,000 number-average molecular weight, and 3.60g of poly(vinyl pyrrolidone) having a number-average molecular weight of 40,000 available from ISP Technologies, Texas City, Texas, are added to a planetary mixing bowl. Next, the dry materials are mixed for 10 minutes. Then, 16g of denatured anhydrous ethyl alcohol is slowly added to the blended materials with continuous mixing for 15 minutes. Then, the freshly prepared wet granulation is passed through a 20 mesh screen (0.841 mm sieve opening) allowed to dry at room temperature for 20 hours and then is passed through a 16 mesh screen (1.00 mm sieve opening). Next, the granulation is transferred to a planetary mixer, mixed and lubricated with 0.6g of magnesium stearate.

Next, a push composition is prepared as follows: first, a binder solution is prepared by dissolving 3g of hydroxypropymethylcellulose possessing a number-average molecular weight of 11,200 in 33.7g of water. Next 0.1g of butylated hydroxytoluene is dissolved in 2g of denatured anhydrous alcohol. Approximately 5g of the hydroxypropylmethylcellulose/water solution is added to the butylated

PCT/US97/03110 WO 97/33566 6

hydroxytoluene/alcohol solution with continuous mixing for 2 to 3 minutes.

Next, the binder solution preparation is completed by adding the remaining 2 hydroxypropylmethylcellulose/water solution to the butylated

hydroxytoluene/alcohol solution, again with continuous mixing thereof. 4

Next, 36g of osmagent sodium chloride is sized using a Quadro Co-mil® mill, to reduce the particle size of the sodium chloride. Next, 1.2g of ferric oxide is passed through a 40 mesh screen (0.387 mm opening).

Then, all the screened materials and 1.2g of naloxone are added to 75.2g 8

of pharmaceutically acceptable poly(ethylene oxide) comprising a 7,000,000 9

number-average molecular weight and to 3g of hydroxypropylmethylcellulose 10

comprising a number-average molecular weight of 11,200 in a fluid bed 11

granular bowl, and the granulation process is initiated to effect granulation. 12

Next, the dry powders are air suspended and mixed for 3 minutes. 13

Then, all the binder solution is sprayed from 3 nozzles onto the 14

powder. The granulating conditions are monitored during the process.

Then, a fluid air mill is used to size the coated granules with an 8 mesh screen (2.38 mm opening screen) and lubricated with 0.28g of magnesium

stearate. 18

3

5

6

15

16

17

19

20

21

22

23

24

25

26

27

28

29

30

Next, the morphine sulfate pentahydrate composition and the displacement antagonist composition are compressed into a bilayer tablet. First, 434 mg of the morphine sulfate pentahydrate composition is added to the die cavity and compressed, then, 260 mg of the displacement antagonist composition is added and the layers pressed under a pressure of approximately 3 tons into a 0.700 inch (1.78cm) x 0.375 inch (0.95 cm) contacting bilayer core with the antagonist separate from the opioid.

The bilayered core arrangement is coated with a semipermeable wall. The wall forming composition comprises 95% cellulose acetate having a 39.8% acetyl content, and 5% polyethylene glycol having a 3350 numberaverage molecular weight. The semipermeable wall-forming composition is dissolved in an acetone:water (95:5 wt:wt) cosolvent to make a 4% solids

solution. The wall-forming composition is sprayed onto and around the 1 bilayer tablets in a coater. Next, two 30 mil (0.762 mm) exit passageways are 2 drilled through the semipermeable wall to connect the opioid-drug layer with 3 the exterior of the dosage system. The residual solvent is removed by drying 4 for 48 hours at 50°C and 50° humidity. The osmotic dosage forms are dried 5 further for 4 hours to 50°C to remove the excess moisture. The dosage form 6 produced by this manufacture comprises in the first composition 28.8% 7 morphine sulfate pentahydrate, 64.2% poly(ethylene oxide) possessing a 200,000 molecular weight, 6% poly(vinyl pyrrolidone) possessing a 40,000 9 molecular weight, and 1% magnesium stearate. The second composition 10 comprises 62.895% poly(ethylene oxide) comprising a 7,000,000 molecular 11 weight, 30% sodium chloride, 5% hydroxypropylmethylcellulose of 11,200 12 molecular weight, 0.78% antagonist naloxone, 1% ferric oxide, 0.075 13 butylated hydroxylotuene, and 0.25% magnesium stearate. The 14 semipermeable wall comprises 95% cellulose acetate comprising a 39.8% 15 acetyl content and 5.0 wt polyethylene glycol of 3350 molecular weight. 16 The dosage form comprises two passageways, 30 mil (0.762 mm) and it has 17

19

18

EXAMPLE 3

a morphine sulfate mean release rate of 5mg/hr.

21 22

23

24

25

26

27

28

29

A dosage form prepared according to the above example is manufactured and further comprises a wall of 60 wt% to 100 wt% of a cellulose polymer which polymer comprises a member selected from the group consisting of a cellulose ester, cellulose diester, cellulose triester, cellulose ether, cellulose ester-ether, cellulose acylate, cellulose diacylate, cellulose triacetate, cellulose triacetate, cellulose acetate, cellulose diacetate, cellulose triacetate, cellulose acetate butyrate, and the like. The wall can also comprise from 0 wt% to 40 wt% of a cellulose ether member selected from the group consisting of hydroxypropylcellulose, hydroxypropylbutylcellulose, and

hydroxypropylmethylcellulose and from 0 wt% to 20 wt% of polyethylene glycol. The total amount of all components comprising the wall is equal to 100 wt%.

The wall in other manufactures, comprises the selectively permeable cellulose ether, ethyl cellulose. The ethyl cellulose comprises an ethoxy group with a degree of substitution, DS, of about 1.4 to 3, equivalent to 40% to 50% ethoxy content, and a viscosity range of 7 to 100 centipoise, or higher. More specifically, the wall comprises 40 wt% to 95 wt% ethyl cellulose, from 5 wt% to 60 wt% polyethylene glycol with the total weight percent of all components comprising the wall equal to 100 wt%. In another manufacture the wall comprises 45 wt% to 80 wt% of ethylcellulose, from 5 wt% to 30 wt% hydroxypropylcellulose, from 2 wt% to 20 wt% of polyvinyl pyrrolidone, with the total amount of all components comprising the wall equal to 100 wt%.

EXAMPLE 4

The antagonist composition according to the above examples wherein the naloxone is replaced by a member selected from the group consisting of naltrexone, nalmefene, nalide, nalmexone, nalorphine, nalpuphine, nalorphine dinicotinate, and the pharmaceutically acceptable salt.

EXAMPLE 5

In the dosage forms provided by the invention, the first composition can comprises 0.1 to 98 wt% opioid base, opioid salt, or opioid derivative; 10 to 95 wt% poly(alkylene oxide) possessing a 100,000 to 650,000 molecular weight or 10 to 95 wt % of a carboxymethylcellulose, such as sodium carboxymethylcellulose, lithium carboxymethylcellulose, or potassium carboxymethylcellulose possessing a 10,000 to 400,000 molecular weight;

- 1 to 20 wt% poly(vinyl pyrrolidone) of 40,000 to 75,000 molecular weight.
- or hydroxypropylcellulose or hydroxypropylmethylcellulose; and 0.10 to
- 3 10 wt% lubricant such as magnesium stearate. In the dosage form,
- the composition comprising the antagonists comprises 30 to 99 wt%
- 5 poly(alkylene oxide) exemplified by poly(ethylene oxide) comprising a
- 6 3,000,000 to 10,000,000 molecular weight, or 20 to 99 wt % of alkali
- 7 carboxymethylcellulose comprising a 450,000 to 2,500,000 molecular weight
- available from Aqualon Co., Hopewell, Virginia; 0 to 80 wt% of an osmagent,
- 9 also known as osmotic effective solute, represented by magnesium sulfate.
- sodium chloride, sodium bicarbonate, sodium succinate, sodium succinate
- hexahydrate, lithium chloride, potassium sulfate, sodium sulfate, lithium
- sulfate, potassium acid phosphate, mannitol, urea, inositol, magnesium
- succinate, tartaric acid, carbohydrates like raffinose, sucrose, glucose,
- lactose, fructose, sodium chloride, fructose, and potassium chloride dextrose;
- 0.25 to 25 wt% of a hydroxyalkylcellulose selected from the group consisting
- of hydroxyethylcellulose, hydroxypropylcellulose, hydroxyisopropylcellulose,
- 17 hydroxybutylcellulose, hydroxypropylmethylcellulose,
- hydroxypropylethylcellulose, hydroxypropylbutylcellulose, which
- hydroxyalkylcellulose comprises a 7,500 to 75,000 molecular weight;
- 20 0 to 5 wt% ferric oxide; 0 to 3 wt% antioxidant represented by d-alpha
- tocopherol, dl-alpha tocopherol, d-alpha tocopherol acetate, dl-alpha-
- tocopherol acetate, d-alpha tocopherol acid succinate, dl-alpha tocopherol
- acid succinate, ascorbic acid, ascorbyl palmitate, butylated hydroxyanisole,
- butylated hydroxytoluene, and propyl gallate; 0.50 to 10 wt% of an
- 25 antagonists, selected from the group consisting of naloxone, naltrexone,
- nalmefene, nalide, nalmexone, nalorphine, naluphine, nalorphine dinicotinate,
- 27 and the pharmaceutically acceptable salts thereof; and 0 to 3 wt% lubricant
- represented by magnesium stearate, calcium stearate, corn starch, potato
- starch, bentonite, citrus pulp, and stearic acid; and with all ingredients in the
- push composition equal to 100 wt%, weight percent.

٠:

WO 97/33566 PCT/US97/03110 10

EXAMPLE 6

1 2

14

15

16

17

18

19

20 21

22

24

25

26

27 28

as ferric oxide.

The therapeutic compositions manufactured by following the above 3 examples and substituting hydromorphone as the opioid and substituting 4 hydromorphone as the opioid provides a hydromorphone drug composition consisting of 1 to 1000 mg of hydromorphone, hydromorphone base. hydromorphone salt, or hydromorphone derivative; at least one of 25 to 7 500 mg poly(alkylene oxide) of 100,000 to 750,000 molecular weight, or 25 to 500 mg of an alkali carboxymethylcellulose of 10,000 to 300,000 molecular weight; at least one of 1 to 50 mg of poly(vinylpyrrolidone) of 10,000 to 10 300,000 molecular weight or 1 to 50 mg of hydroxypropylcellulose or 11 hydroxypropylalkylcellulose of 7,500 to 75,000 molecular weight; 0 to 10 mg 12 of a lubricant such as magnesium stearate; and 0 to 50 mg of a colorant such 13

The dosage form, provided by the example, comprises a push composition that forms a second layer consisting of at least one of 15 to 750 mg of a poly(alkylene oxide) of 3,000,000 to 7,750,000 molecular weight. or 15 to 750 mg of a carboxymethylcellulose such as sodium carboxymethylcellulose, and potassium carboxymethylcellulose of 450,000 to 2,500,000 molecular weight; 0 to 75 mg of an osmagent, also known as osmotically solute represented by magnesium sulfate, sodium chloride, sodium bicarbonate, sodium succinate, sodium succinate hexahydrate, lithium chloride, potassium sulfate, sodium sulfate, lithium sulfate, potassium acid phosphate, mannitol, urea, inositol, magnesium succinate, tartaric acid, carbohydrates like raffinose, sucrose, glucose, lactose, fructose, sodium chloride, and fructose, potassium chloride and dextrose; 1 to 50 mg of a hydroxyalkylcellulose selected from the group consisting of hydroxyethylcellulose, hydroxypropylcellulose, hydroxyisopropylcellulose,

hydroxybutylcellulose, hydroxypropylmethyl-cellulose,

- hydroxypropylethylcellulose, hydroxypropylbuitylcellulose which
- 2 hydroxyalkylcellulose comprises a 7,500 to 75,000 molecular weight;
- 3 0 to 10 mg and more preferred 0.05 to 7.5 mg of an antioxidant represented
- by d-alpha tocopherol acetate, dl-alpha tocopherol, ascorbyl palmitate,
- butylated hydroxyanidole, butylated hydroxytoluene and propyl gallate;
- 6 0 to 10 mg of a lubricant represented by magnesium stearate, calcium
- stearate, corn starch, potato starch, bentonite, citrus pulp, and stearic acid;
- 8 0 to 10 mg of a colorant; and 0.01 to 20 mg of an antagonist selected from
- 9 the group consisting of naloxone, naltrexone, nalmefene, nalide, nalmexone,

nalorphine, and naluphine.

11

EXAMPLE 7

13 14

15

16

17

18

19

20

21

22

23

25

26

27

28 29

30

The dosage form, further provided by the invention, comprises a pushdisplacement composition for pushing the hydromorphone composition from the dosage form consisting of at least one of 15 to 500 mg of a poly(alkylene oxide) of 3,000,000 to 10,000,000 molecular weight, or 15 to 750 mg of an alkali carboxymethylcellulose such as sodium carboxymethylcellulose, and potassium carboxymethylcellulose of 450,000 to 2,500,000 molecular weight; 0 to 500 mg and more preferred 5 mg to 350 mg of an osmagent, also known as osmotically solute represented by magnesium sulfate, sodium chloride, sodium bicarbonate, sodium succinate, sodium succinate hexahydrate, lithium chloride, potassium sulfate, sodium sulfate, lithium sulfate, potassium acid phosphate, mannitol, urea, inositol, magnesium succinate, tartaric acid, carbohydrates like raffinose, sucrose, glucose, lactose, fructose, sodium chloride and fructose, potassium chloride and dextrose; 0.01 to 20 mg of an antagonist for an opioid; 1 to 50 mg of a hydroxyalkylcellulose selected from the group consisting of hydroxyethylcellulose, hydroxypropylcellulose, hydroxyisopropylcellulose, hydroxybutylcellulose,

hydroxypropylmethylcellulose, hydroxypropylethylcellulose,

29

1	hydroxypropylbuitylcellulose which hydroxyalkylcellulose comprises a 7,500 to			
2	75,000 molecular weight; 0 to 10 mg of an antioxidant represented by d-alpha			
3	tocopherol acetate, dl-alpha tocopherol, ascorbyl palmitate, ascorbic acid,			
4	butylated hydroxyanidole, butylated hydroxytoluene and propyl gallate;			
5	0 to 10 mg of a lubricant represented by magnesium stearate, calcium			
6	stearate, corn starch, potato starch, bentonite, citrus pulp, and stearic acid;			
7	and 0 to 10 mg of a colorant.			
8				
9	EXAMPLE 8			
10				
11	The dosage form, as described in Example 2, except no colorant is			
12	present in the push composition. Also, rather than two 30 mil exit			
13	passageways drilled through the semipermeable wall on the opioid-drug			
14	layer, one 30 mil exit passageway is drilled on the opioid-drug layer and one			
15	30 mil exit passageway is drilled on the push layer.			
16				
17	EXAMPLE 9			
18				
19	Same as Example 8, except the poly(ethylene oxide) comprising a			
20	5,000,000 to 15,000,000 number-average molecular weight in the push			
21	composition.			
22				
23	ADDITIONAL DISCLOSURE OF THE INVENTION			
24				
25	The expression, "exit means," for the dosage form as used, comprises			
26	means and methods suitable for the metered release of beneficial drug			
27	morphine from the dosage form. The exit means comprises at least one			
28	passageway, orifice, or the like, through the wall for communicating with			

morphine in the dosage form. The expression, "at least one passageway,"

comprises aperture, orifice, bore, micropore, porous composition, porous

WO 97/33566 PCT/US97/03110

element through which the drug can migrate, hollow fiber, capillary tube, 1

- porous overlay, porous insert, and the like. The expression also includes a 2
- material that erodes or is leached from the wall in the fluid environment of use 3
- to produce least one passageway in the dosage form. Representative 4
- materials suitable for forming at least one passageway, or a multiplicity of 5
- passageways, include an erodible poly(glycolic) acid, or poly(lactic) acid 6
- member in the wall, a gelatinous filament, poly(vinyl alcohol), leachable 7
- materials such as fluid removable pore forming polysaccharides, salts, oxides, 8
- or the like. A passageway or a plurality of passageways can be formed by
- 10 leaching a material such as sorbitol, lactose, fructose, maltose, mannose,
- glucose, and the like from the wall. The passageway can have any shape 11
- such as round, triangular, square, elliptical, and the like, for assisting in the 12
- metered release of the opioid-drug from the dosage form. The dosage from 13
- can be constructed with one or more passageways in spaced apart relations, 14
- or more than one passageway on a single surface of a dosage form. 15
- Passageways and equipment for forming passageways are disclosed 16
- in U.S. Pat. Nos. 3,845,770; 3,916,899; 4,063,064 and 4,088,864. 17
- Passageways of govern size formed by leaching are disclosed in 18
- U.S. Pat. Nos. 4,200,098 and 4,285,987. 19
- Exemplary solvents used for the present purpose comprise inorganic 20
- and organic solvents that do not adversely harm the materials and the final 21
- wall or the final compositions in the dosage form. The solvents broadly 22
- include members selected from the group consisting of aqueous solvents, 23
- alcohols, ketones, esters, ethers, aliphatic hydrocarbons, halogenated 24
- solvents, cycloaliphatics, aromatics, heterocyclic solvents, and mixtures 25
- thereof. Typical solvents include acetone, diacetone alcohol, methanol, 26
- ethanol, butyl alcohol, methyl acetate, ethyl acetate, isopropyl acetate, n-butyl 27
- acetate, methyl isobutyl ketone, methyl propyl ketone, n-hexane, n-heptane, 28
- ethylene glycol monoethyl ether, ethylene glycol monoethyl acetate, 29
- methylene dichloride, ethylene dichloride, propylene dichloride, carbon 30

tetrachloride, chloroform, nitroethane, nitropropane, tetrachloroethane, ethyl

ether, isopropyl ether, cyclo-hexane, cyclo-octane, benzene, toluene,

naphtha, 1,4-dioxane, tetrahydrofuran, diglyme, aqueous and nonaqueous

mixtures thereof, such as acetone and water, acetone and methanol, acetone

and ethyl alcohol, methylene dichloride and methanol, and ethylene dichloride

6 and methanol.

7 8

5

DISCLOSURE FOR USING THE INVENTION

9

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

The invention concerns a method for administering an opioid analgesic to a patient, from a dosage form characterized by a separate composition comprising an antagonist for an opioid to substantially lessen opioid abuse.

The method provides administering 10 ng to 750 mg of an opioid analgesic to the patient from a dosage form comprising a semipermeable wall permeable to aqueous-biological fluid and impervious to an opicid; an opioid composition, which dosage form comprises 10 to 98 wt% opioid, 10 to 80 wt% poly(alkylene oxide) possessing a 100,000 to 650,000 molecular weight, and 1 to 20 wt% poly(vinyl pyrrolidone) of 40,000 to 75,000 molecular weight, and a push-displacement composition comprising 40 to 90 wt% poly(alkylene oxide) comprising a 3,000,000 to 15,000,000 molecular weight, 0 to 80 wt% of an osmagent, and 0.25 to 25 wt% of a hydroxyalkylcellulose possessing a 7,500 to 75,000 molecular weight, and 0.01 to 10% of an antagonist maintained in the antagonist composition; and 0 to 5% of a colorant which opioid composition and push-displacement compositions are surrounded by the semipermeable wall; and exit means in the wall for delivering the opioid from the dosage form, by imbibing fluid through the wall into the dosage from causing the opioid composition, and causing the push-displacement composition to expand and push the opioid drug composition through the exit means, whereby through the combined

19

20

21

22

23

operations of the dosage form, the opioid analgesic is delivered at a

therapeutically effective dose at a controlled rate over a sustained period of time. 4 The invention is characterized additionally by the invention's ability to administer an opioid analgesic to a patient in need of an opioid analgesic 5 from a dosage form while simultaneously maintaining an opioid antagonist 6 in the dosage form to prevent opioid abuse. Thus, the dosage form of the 7 present invention provides the following advantages: (1) a therapeutic opioid 8 analgesic effect that is essentially constant; (2) smoothness and consistency 9 in the level of opioid analgesic delivered to the blood of the patient; 10 (3) reduced potential for misuse or abuse of the opioid-containing dosage 11 form; (4) maintaining the opioid and antagonist separate in the dosage form; 12 (5) decrease the risk of overdosing and resulting toxic reactions; 13 (6) improvement in patient compliance accompanied by a recommended 14 therapy program; (7) eliminate undesirable interactions and reactions 15 between the opioid and the opioid antagonist contained in the dosage form; 16 (8) administering a drug opioid composition free of an antagonist; and 17

Inasmuch as the foregoing specification comprises disclosed embodiments, it is understood what variations and modifications may be made herein, in accordance with the principles disclosed, without departing from the invention.

opioid maintenance as both clinical inpatient and clinical outpatient treatment.

(9) improve the treatment of an opioid addict to correctly and safely use

I	We claim:
?	
3	A dosage form comprising:
•	(1) a wall comprising a semipermeable composition, which wall
5	surrounds:
ŝ	(2) a bilayer core comprising:
7	(a) a first layer comprising an analgesic opioid;
В	(b) a second layer in contact with the first layer,
9	comprising 40 to 99 wt% of a poly(alkylene oxide) possessing a 3,000,000 to
0	10,000,000 number average molecular weight, and 0.25 to 25 wt% of a
1	hydroxyalkylcellulose possessing a number average molecular weight of
2	7,500 to 75,000, and wherein the second layer is characterized by comprising
3	0.75 to 10 wt% of an antagonist selected from the group consisting of
4	naltrexone, naloxone, nalmefene, nalide, nalmexone, nalorphine, and
5	naluphine; and,
6	(3) an exit in the wall for releasing the opioid analgesic from the
7	dosage form.
8	The dosage form according to claim 1, wherein the antagonist is
9	present as the pharmaceutically acceptable salt.
0	The dosage form according to claim 1 wherein the second layer
21	comprises an osmagent.
22	4. The dosage form according to claim 1, wherein the analgesic opioid
23	comprises a member selected from the group consisting of apomorphine,
24	apocodeine, codeine, dihydrocodeine, dihydromorphine, hydrocodone,
25	hydroxymethylmorphian, hydromorphone, methylmorphine, morphine,
26	normorphine, oxycodone, benzylmorphine, and oxymorphone.
27	The dosage form according to claim 1, wherein the analgesic opioid
28	comprises a member selected from the group consisting of alfentanil,
29	fentanyl, lofentanil, and sufentanil.

1	6. The dosage form according to claim 1 wherein the second layer
2	comprises an antioxidant.
3	7. The dosage form according to claim 1, wherein the first layer
4	comprises a member selected from the group consisting of allylprodine,
5	alphaprodine, anileridine, bezitramide, buprenorphine, butophanol,
6	clonitazene, cyclorphan, cyprenorphine, desomorphine, dextromoramide,
7	dezocine, diampromide, diminoxadol, eptazocine, ethylmorphone,
8	hydroxypethidine, levophenacylmorphan, levorphand, necomorphine,
9	normethadone, pholocodine, and profadol, and wherein the first layer
10	composition is free of antagonist.
11	8. A dosage form comprising:
12	(1) a wall comprising a semipermeable composition, which wall
13	surrounds:
14	(2) a bilayer core comprising:
15	(a) a first layer comprising an analgesic opioid;
16	(b) a second layer in contact with the first layer comprising 20 to
17	99 wt% of a poly(carboxymethylcellulose) comprising a 450,000 to 2,500,000
18	number average molecular weight, and 0.25 to 25 wt% of a
19	hydroxyalkylcellulose possessing a number average molecular weight of
20	7,500 to 75,000. and wherein the second layer is characterized by comprising
21	0.75 to 10 wt% of an antagonist selected from the group consisting of
22	naltrexone, naloxone, nalmefene, nalide, nalmexone, nalorphine, and
23	naluphine; and,
24	(3) an exit passageway in the wall for releasing the opioid analgesic
25	from the dosage form.
26	9. The dosage form according to claim 8, wherein the antagonist is
27	present as the pharmaceutically acceptable salt

- 10. The dosage form according to claim 8, wherein the analgesic
 2 opioid comprises a member selected from the group consisting of
 3 apomorphine, apocodeine, codeine, dihydrocodeine, dihydromorphine,
 4 hydrocodone, hydroxymethylmorphan, hydromorphone, methylmorphine,
 5 morphine, normorphine, oxycodone, benzylmorphine, and oxymorphone.
 - 11. The dosage form according to claim 8, wherein the analgesic opioid comprises a member selected from the group consisting of alfentanil, fentanyl, lofentanil, and sufentanil.
 - 12. The dosage form according to claim 8, wherein the first layer is a composition comprising a member selected from the group consisting of allylprodine, alphaprodine, anileridine, bezitramide, buprenorphine, butophanol, clonitazene, cyclorphan, cyprenorphine, desmorphine, dextromoramide, dezocine, diampromide, diminoxadol, eptazocine, ehtylmorphine, hydroxypethidine, levorphenacylmorphan, levorphanol, necomorphine, normethadone, pholocodine, and profadol, and wherein the first layer composition is free of antagonist and pressed as a tablet.
 - 13. The dosage form according to claim 8 wherein the dosage form comprises a member selected from the group consisting of d-alpha tocopherol acetate, dl-alpha tocopherol, ascorbyl plamitate, ascorbic acid, butylated hydroxyanidate, butylated hydroxylotuene, and propylgallate.
 - 14. A composition of matter comprising 10 ng to 275 mg of naloxone and 15 mg to 750 mg of a poly(alkylene oxide) comprising a 3,000,000 to 10,000,000 molecular weight.
 - 15. The composition of matter according to claim 14, wherein the nalcyone is replaced by a member selected from the group consisting of naltrexone, nalmefene, nalide, nalmexone, nalorphine, and nalpuphine, and the composition is compressed into a tablet.
 - 16. A composition of matter comprising 10 ng to 275 mg of naloxone and 15 to 750 mg of a poly(carboxymethylcellulose) comprising a 450,000 to 2,500,000 molecular weight.

- 1 17. The composition of matter according to claim 16, wherein the naloxone is replaced by a member selected from the group consisting of naltrexone, nalmefene, nalide, nalmexane, nalorphine, and nalpuphine and the composition is compressed into a tablet.
- 18. A composition of matter comprising 10 ng to 275 mg of naloxone, 15 mg to 750 mg of a poly(alkylene oxide) comprising a 3,000,000 to 10,000,000 molecular weight, 5 mg to 350 mg of an osmagent, and 0.05 mg to 7.5 mg of an antioxidant.
- 19. A composite of matter comprising 10 ng to 275 mg of naloxone, 15 mg to 750 mg of a poly(carboxymethylcellulose) comprising a 450,000 to 11 2,500,000 molecular weight, 5 mg to 350 mg of an osmagent and 0.05 mg to 12 7.5 mg of an antioxident.